

FIXED DISPLACEMENT AXIAL PISTON MOTORS

TMF 200 (Ex 20 - 30)

ORDER CODE

TMF	20	SS3	F1	RC	00
1	2	3	4	5	6

Pag.

1 - Motor series		
TMF	= Fixed displacement motor	3-4
2 - Motor displacement		
20	= 20 cm ³ /n	8
30	= 30 cm ³ /n	8
3 - Shaft		
SS3	= Splined shaft Z13 16 / 32 D.P.	11
PS2	= Parallel keyed shaft 22,2 diam.	11
4 - Flange		
F1	= SAE A 2 holes - pilot diam.82,5 mm.	
5 - Main connection		
RC	= Rear ports	5
SC	= Side ports	5
6 - Optional		
00	= Without optionals	
RB	= Roller bearing	
FB	= Adaptor flange SAE B	
FS	= Shim flange SAE A	

VARIABLE DISPLACEMENT AXIAL PISTON MOTORS

TMV 250 (Ex 20 - 30) ORDER CODE

TMV	20	SS3	F1	RC	DM	OA	00
1	2	3	4	5	6	7	8

Pag.

1 - Motor series	
TMV = Variable displacement motor	3-6
2 - Motor displacement	
20 = 8 - 20 cm ³ /n	8
30 = 12 - 30 cm ³ /n	8
3 - Shaft	
SS3 = Splined shaft Z13 16 / 32 D.P.	11
PS2 = Parallel keyed shaft 22,2 diam.	11
4 - Flange	
F1 = SAE A 2 holes - pilot diam.82,5 mm.	
5 - Main connection	
RC = Rear ports	7
SC = Side ports	7
6 - Controls	
DM = Direct mechanical	7
LC = Control lever	7
7 - Control devices position	
OA = Position A	9
OB = Position B	9
8 - Optional	
00 = Without optionals	
RB = Roller bearing	
FB = Adaptor flange SAE B	
FS = Shim flange SAE A	